



ITEM	NAME OF PART	MATERIAL	NOTES
2	Pin header	Copper	Sn Plated
1	Housing	PA66	UL94V-0

UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/15	/	300/10
VDE 标准 VDE Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	II/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	/	320/20	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	/	4	/
爬距/C爬距(mm)/绝缘范围/Poles	5.08/N=02~24P		
使用温度范围/Operating Temperature(°C)	-40°C~+105°C		
符合RoHS环保要求/Conform to RoHS	Yes		

MATERIAL: SURFACE:

MAT NO.:

STATUS:

APPD:

CHKD:

DRT:



® 宁波三安电子科技有限公司  
Sanan Electrical Technology Co., Ltd

NAME: ZESARC-5.08-XXP-1Y-100A(H)

DRAWING NO.:

SCALE:

TYPE:

SIZE: A4

mm  
(inch)



REV  
SHEET  
1/1

公差/General	tolerances(mm)
0	>3
~	>6
~	>10
~	>18
~	>30
~	>50
~	>80
~	>120
~	>180
~	>250
~	>315
~	>400
~	>500
±Z	±Z

0.1/10  
±Z